



## Ultra1Plus™ SAE 75W-90 Synthetic gear oil API GL-4

### Product description

**Ultra1Plus™ SAE 75W-90 Synthetic Gear Oil, API GL-4** is formulated with synthetic base oils and specialty performance additives to provide improved high-temperature thermal and oxidative stability in a wide range of operating conditions. Specialty anti-scuffing additives and friction modifiers provide advanced protection and lubricity in extreme pressure conditions. Additionally, Ultra1Plus™ SAE 75W-90 Synthetic Gear Oil, API GL-4 is highly shear stable while also resisting rust, oxidation, foaming, and varnish.

**Ultra1Plus™ SAE 75W-90 Synthetic Gear Oil, API GL-4** is designed for use in all seasons and exceed the year-around, all-weather performance viscosity requirements of SAE J306 as well as the rigorous performance requirements of API GL-4.

### Product features & benefits

- Extended gear and bearing life due to minimal deposits.
- Longer seal life.
- Increased load-carrying capability.
- Helps to reduce operating costs.
- Contribution to reduced wear and ease of startup.

### Product codes

Presentation	SKU	UPC
1.05 QT / 1 Liter	UFS7590GL4L	810050654326
5 Gallon Pail	UFS7590GL4P	810050654302
55 Gallon Drum	UFS7590GL4D	810050654296

### Product features & benefits

API GL-4

### Typical properties

SAE J306 Viscosity Grade	75W-90
Appearance	Yellow, transparent liquid
Viscosity @ 40°C, cSt, ASTM D445	113.2
Viscosity @ 100°C, cSt, ASTM D445	15.5
Viscosity index, ASTM D2270	145
Flash point, °C, ASTM D92	205
Pour point, °C, ASTM D97	-50



Revised: 01/07/2021