



RED LINE MTL® 75W80 GL-4 GEAR OIL



- Popular for BMW, Honda and Acura, Ford Focus, late-model Mini Cooper, Land Rover/Range Rover LT77S, Dodge & Jeep NV1500, NV3500 , NV3550 and NV5600 truck transmissions
- Popular replacement for and improvement over GM Synchronesh® (#12345349), Auto-Trak II® (#12378508) and Chrysler spec MS-9224
- **Safe for brass synchros, as it lacks the reactive sulfurs found in most GL-5 oils that cause damage**
- Offers quicker shifts, perfect synchronizer coefficient of friction
- Eliminates notchy shifting, even when cold
- High performance gear protection and longer synchro life
- Satisfies the gear oil viscosity requirements of 75W, 80W, and motor oil viscosities of SAE 30, 10W30 and 5W30
- Recommended for GL-1, GL-3 and GL-4 applications as well as where most special synchronesh fluids are specified

RECOMMENDED FOR:

Suitable replacement for:	4773167 4874465	ESD-M2C-186-A	12378508 12799117 21018899	Honda/Acura 08798-9013A 08798-9016A 08798-9016	MB 235.10 900 26 03-15 A 001 989 85 03	Multi Gear Oil ECO MZ313501	Renault Clio PT 77 11	MTF 97309-10
API GL-4 / GL-3 / GL-1 SAE 80/80W/75W80 SAE 30/5W30/10W30	Citroen	Genuine Mtf	88900333 88900399 88900402	4928271 Genuine MTF		Nissan ETL 8997B KE 916-99033 MTF TL/JR	Saab MTF0063	VW/Audi G 052 171 G 052 176 G 052 532 G 055 532
Alfa Romeo	Dacia	GM 10-4006 10-4014 10-4017	89021808 Auto-Trak II BOT 0063	Mini/BMW 83 22 0 403 247 83 22 0 140 516 83 22 2 344 589			Tata	
Chrysler MS9224 MS-9417 MS-9440 4874464 05179014AA 4761523	Daewoo	1052931 9985648 9986117	MTF 0063 Synchronesh	Jaguar/Land Rover/Range Rover LR006247 MTF 0063	MTF-2 MTF 94	Opel/Vauxhall 09 120 541	Volvo 1161745 1161645 97308 1151324-7 1161423-7 M2C 200-C3	
	Fiat	10953626 E5RY-19C547-A ESD-M2C-186-A	Holden	Mazda 0000-77-5W80-QT	Mitsubishi Genuine MTF MTX	Peugeot/Citroen PSA B71 2330 75w80		

TYPICAL PROPERTIES:

API Service Class	GL-4
SAE Viscosity Grade (Motor Oil)	5W30
SAE Viscosity Grade (Gear Oil)	75W80
Vis @ 100°C, cSt	10.4
Vis @ 40°C, cSt	50.8
Viscosity Index	201
Pour Point, °C	-50
Pour Point, °F	-58
Brookfield Viscosity @ -40°C, Poise	120

PACKAGE SIZES:

- 50204 - MTL 75W80 GL-4 - quart
- 50205 - MTL 75W80 GL-4 - 1 gallon
- 50206 - MTL 75W80 GL-4 - 5 gallon
- 50207 - MTL 75W80 GL-4 - 16 gallon
- 50208 - MTL 75W80 GL-4 - 55 gallon

ABOUT RED LINE GEAR OIL FOR MANUAL TRANSMISSIONS

- Appropriate coefficient of friction for most manual transmission synchronizers (other synthetic gear oils are often too slippery for proper synchro engagement)
- Red Line offers lubricants to pinpoint nearly every transmission application
- MTL, MT-85 and MT-90 are not for use in differentials with hypoid gears
- Excellent gear and synchro protection, balanced slipperiness for easier shifting in cold climates
- Excellent for high- and low-mile transmissions
- Compatible with petroleums and other synthetics

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM